

Exit & Emergency Luminaires

LFSPOT

Twin LED Emergency Floodlight designed to provide indirect emergency lighting to large, high ceiling areas, such as factories and warehouses.

Features and Benefits

- 2x 3W LED Flood lights with low power consumption
- Excellent illumination in mains and emergency modes
- In-built Sentinel automatic self testing capability
- Low standby power consumption
- High Temperature components for extended life
- Designed and manufactured in accordance to AS/NZS 2293



LFSPOT		
Input	Operating Voltage / Frequency	230V / 50Hz
Output	Light Source	LED
	Lumen Output (per spot light)	137lm
	Function	Non-Maintained
	Power Consumption (LEDs)	6W
Battery	Type	LiFePO ₄
	Charger	Variable current CV
	Protection	Overcharge and low voltage disconnect
	Autonomy Duration	2 hours*
Physical	IP Classification	IP20
	Weight	1.9kg
	Length	270mm
	Width	85mm
	Height	254mm
	Construction	Body: Powder coated folded sheet metal Floodlights: Acrylic Lens
Installation	Mounting	Surface
Environment	Temperature	0°C - 40°C
	Relative Humidity	0 - 95%
Conformance	Standards	AS/NZS 2293, AS/NZS 60598, AS/NZS CISPR15
Intelligence	Sentinel	Yes
	WiNetRF	No
Warranty	Duration	Fitting: 3 Years / Battery: 2 Years

*Guaranteed to meet runtime requirements of AS/NZ 2293 throughout warranty duration.

ACCESSORY	DESCRIPTION
32621	Replacement Battery for LFSPOT